

SURFACE RENEWAL PRODUCTS HOFMANN STEEL STICK

INTRODUCTION:

It is a high strength metal filled molecular technology system which gets cured within 10Minutes. It is fast it mix and fast to apply. It can be machined, drilled or tapped. It is an excellent product for emergency low-cost repair to all metals.

FEATURE & BENEFITS:

- (1) Fast and emergency repair that can reduce the down time.
- (2) Fast mixing and easy application, no two part mixing, just cut, knead and apply.
- (3) Will bond to almost all material.
- (4) Equipment can be put to operation in 10 minutes time.

TYPICAL APPLICATION:

Emergency repair to Elbow, Pipes, Tanks, Pumps, Vessels, Gearboxes and many other emergency applications even online within 10-15 minutes shut down.

PHYSICAL PROPERTIES:

Compressive strength	: 400 Kg/cm ²
Tensile Shear strength(Bonding)	: 110 kg/cm ²
Max. Operating Temperature	: 100 deg. C
Working time at 30deg.C	: 3 to 4 minutes.
Curing time at 30deg. C	: 10 minutes.
Hardness Shore D	: 75 D
Mix Ratio	: NO MIXING
Specific volume	: 425cc/Kg.

FROM.
HOFMANN ENGG. & MKTG. P. LTD.
 307, shubham complex, vastrapur,
 AHMEDABAD: 380 061.
 TEL: 079-2685 3867
 Telefax : 079-2685 0175
 E MAIL: info@hofmannindia.com
 Web: www.hofmannindia.com

AUTHORISED DEALER: